



L8000 - C2 LoVo Interior Latex Non-Reflective Flat Technical Specifications

PRODUCT DESCRIPTION			
L-8000 -LoVo Interior Latex Non-Reflective Flat is a premium low VOC coating designed to provide an exceptional non-reflective finish on interior walls and particularly the fifth wall, the ceilings. Outstanding application properties result in a smooth, beautiful finish			
SPECIFICATIONS			
Type:	100% Co-Polymer Blend	Dry Time - Touch:	30 Minutes
Sizes:	1's, 5's and Quarts	Dry Time - Recoat:	1-3 Hours
Bases:	White, Pastel, Midtone, Accent	Full Service:	7 Days
Gloss:	5.0 max @ 85°	Flash Point:	None
		VOC:	Less than 50 g/liter
		% Solids Volume:	42% +/- .5
		Weight Per Gallon:	11.60 +/- .2
PRODUCT USE			
<p style="text-align: center;">Surface preparation</p> <p>Remove from the surface any and all adhesion preventing contaminants. (Dirt, chalk, dust, oil, grease, wax, etc.) Scuff sand all glossy areas to promote adhesion. See your local C2 Paint dealer for expert help on proper primers for specific surfaces and surface repair.</p> <p>New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints and repaired areas with C₂ LoVo Drywall Primer, after dry apply one coat of C₂ LoVo Drywall primer to the entire surface. Finish with one or two coats of C₂ LoVo Interior Latex Non-Reflective Flat.</p> <p>Previously Painted Surfaces: Remove loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C₂ LoVo Drywall Primer. When painting over dark colors, best results are achieved by priming entire surface. Finish with one or two coats of C₂ LoVo Interior Latex Non-Reflective Flat.</p>		<p style="text-align: center;">Application</p> <p>L8000 LoVo Interior Latex Non-Reflective Flat may be applied by roller (no more than 3/8 inch nap), brush (synthetic) or spray.</p> <p>Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)</p> <p>Thinning: Do not thin.</p> <p>Airless Spray: Use a 12 to 15 mil size tip.</p> <p>Cleanup: Clean painting equipment and spills immediately using warm soapy water.</p> <p>Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Deep colors in a flat or matte finish may burnish. For a non-burnishing finish, choose C₂ LoVo Premium Eggshell. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p>Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C₂ dealer for disposal recommendations in your area.</p>	

C2 LoVo is formulated without lead or mercury or HAPs

UPDATED FEBRUARY 2008