



C2085 – Interior ACS Primer Technical Specifications

PRODUCT DESCRIPTION			
C2085 Interior ACS Primer is a co-polymer acrylic emulsion primer exhibiting excellent sealing characteristics for application in most residential and commercial settings. C2085 is part of C₂'s Accent Color System and is not to be applied untinted.			
SPECIFICATIONS			
Type:	Co-Polymer Acrylic	Dry Time - Touch:	30 Minutes
Sizes:	5's, 1's and Quarts	Dry Time - Recoat:	2-4 Hours
Bases:	Accent	Full Service:	14 Days
Gloss:	3%-4% @ 60°	Flash Point:	None
	4%-6% @ 85°	VOC:	129 gm/L
		% Solids Volume:	33.8 +/- .5
		Weight Per Gallon:	10.22 +/- .2
PRODUCT USE			
<p style="text-align: center; color: red; margin: 0;">Surface preparation</p> <p>Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.</p> <p>New Plaster & Drywall: Plaster must be completely cured (30 days) before priming. Sand smooth drywall tape joints and other repaired areas. Spot prime and then apply one coat of C2085 to the entire surface.</p> <p>New Wood: For best results sand entire surface and apply one coat of C2010 Latex Enamel Undercoater. Sand smooth and apply one coat of C2085 and finish with the desired C₂ Interior product.</p> <p>Previously Painted Surfaces: Remove loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C2085. Apply one coat of C2085 to the entire surface and finish with the appropriate C₂ interior paint.</p>		<p style="text-align: center; color: red; margin: 0;">Application</p> <p>C2085 Interior ACS Primer may be applied by roller (no more than 3/8 inch nap), brush (synthetic) or spray.</p> <p>Spreading Rate: The C2 Accent Color System is designed to produce rich, vibrant colors with a minimum number of coats of primer and paint. Full heavy coats of primer are required to produce a solid base color. Product should be applied at a maximum rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)</p> <p>Thinning: Do not thin.</p> <p>Airless Spray: Use a 12 to 15 mil size tip.</p> <p>Cleanup: Clean painting equipment and spills immediately using warm soapy water.</p> <p>Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p>Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C₂ dealer for disposal recommendations in your area.</p>	

C2 Paint is formulated without lead or mercury