



C3085 – Exterior ACS Primer Technical Specifications

| PRODUCT DESCRIPTION | | | |
|---|---------------------|---|-------------|
| <p>C3085 Exterior ACS Primer is a 100% acrylic primer with excellent sealing and stain blocking properties for application in most residential or commercial settings. C3085 is specifically formulated to seal most common exterior stains and will adhere tenaciously to a variety of surfaces. C3085 is part of C₂'s Accent Color System and is not to be applied untinted.</p> | | | |
| SPECIFICATIONS | | | |
| Type: | Pure Acrylic | Dry Time - Touch: | 30 Minutes |
| Sizes: | 5's, 1's and Quarts | Dry Time - Recoat: | 2-4 Hours |
| Bases: | Accent | Full Service: | 14 Days |
| Gloss: | 10%-15% @ 60° | Flash Point: | None |
| | 20%-30% @ 85° | VOC: | 126 gm/L |
| | | % Solids Volume: | 41.4 +/- .5 |
| | | Weight Per Gallon: | 9.75 +/- .2 |
| PRODUCT USE | | | |
| <p style="text-align: center; color: red; font-weight: bold;">Surface preparation</p> <p>Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Remove mildew using a chlorine bleach solution of 1 part bleach to 4 parts water. Patch holes and cracks, sand smooth and remove dust.</p> <p>New Wood: Sand smooth and remove dust. Spot prime knots with C₂ Exterior Alkyd Primer. Apply one coat of C3085 to the entire surface. Note: For severely staining wood, multiple coats may be required. Finish with the appropriate C₂ exterior house paint</p> <p>Previously Painted Surfaces: Remove loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C3085. Apply one coat of C3085 to the entire surface and finish with the appropriate C₂ exterior house paint.</p> <p>Galvanized Metal: Clean surfaces thoroughly using a strong solvent. Apply one coat of C3085.</p> <p>Masonry: New masonry must be fully cured (90 days). Fill blocks if required and apply one coat of C3085.</p> | | <p style="text-align: center; color: red; font-weight: bold;">Application</p> <p>C3085 Exterior ACS Primer may be applied by roller (no more than 3/8 inch nap), brush (synthetic) or spray.</p> <p>Spreading Rate: The C2 Accent Color System is designed to produce rich, vibrant colors with a minimum number of coats of primer and paint. Full heavy coats of primer are required to produce a solid base color. Product should be applied at a maximum rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)</p> <p>Thinning: Do not thin.</p> <p>Airless Spray: Use a 12 to 15 mil size tip.</p> <p>Cleanup: Clean painting equipment and spills immediately using warm soapy water.</p> <p>Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p>Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C₂ dealer for disposal recommendations in your area.</p> | |

C2 Paint is formulated without lead or mercury